

Electro-Chemical Marking "Made in Germany"

- * Electrolytic marking of metal items of different shapes and sizes with: letters and numbers, graphics, trade marks, scales, data and logos.
- * Suitable for medium and large size series, expandable to semi-automatic machine.
- * Choice of light / dark markings, exact adjustment of the marking time.
- * Recommended for steel, aluminium, non-ferrous metals and large markings.
- * Adjustable operation Voltage: 12 / 18 / 24 V.
- * End of marking time is indicated by an optical and acoustic signal. A class better!
- * Versatile, sturdy and durable.
- * Warranty period: 3 years.

It's so simple and quick: Electrolytic marking on flat, convex, concave or round surfaces.



In Grubenäcker 1 DE - 78532 Tuttlingen



+49 (0)7461 9472-20

New:

YIR

- * Controlled by micro-processor
- * Illuminated, digital display of all parameters
- * Electronic short-circuit protection
- * Integrated contact plate



+49 (0)7461 9472-0

www.schilling-marking.de info@schilling-marking.de



Optional Accessories



Art.-No.: 56.072



Art.-No.: 56.073



Art.-No.: 56.075



Art.-No.: 35.005

Workholding Unit for small series

- * Exact alignment of the parts to the stencil
- * For small series
- * Accurate adjustment of the stencil
- * Fast replacement of the jigs

Etch-Station M1 with supply of Electrolyte

- * With automatic supply of Electrolyte
- * For small and mid-size series
- * Exact alignment of the workpiece to the stencil
- * Accurate adjustment of the stencil
- * Fast replacement of the jigs

Pneumatic Work Holder for semi auto operation

- * For medium and mass production
- * Expandable to semi or fully automatic operation
- * Constant pressure force
- * Accurate adjustment of the stencil
- * Fast replacement of the jigs
- * Exact alignment of the parts to the stencil
- * Adjustable movement range in Z-axis up to 370mm

Electrolyte Pump for Pneumatic Work Holder

- * Fine dosage of Electrolyte
- * Always the same results due to a constant supply of Electrolyte
- * Pump function of Electrolyte liquid forwards / backwards

SIGNOMAT S100 - Technical Specifications	
Dimensions W,H,D:	265, 95, 275 mm
Mains voltage:	115/230 V 50/60 Hz (automatic recognition)
Marking voltage:	12 V / 18 V / 24 V
Marking current:	3,9 A
Current types:	dark or light
Output:	100 VA
Weight:	4,4 kg
Noise level:	20 dB
Operation modes:	 manual stamp with automatic start-up manual marking together with a foot switch ppeumatic stroke started by a foot switch

pneumatic stroke started by a foot switch

K:\Prospekte\Signiertechnik\Prospekt-ErstellungS100_GB.cdr



Schilling Marking Systems GmbH In Grubenäcker 1 DE - 78532 Tuttlingen Edition: 04/14

+49 (0)7461 9472-0

YIR

+49 (0)7461 9472-20



Technical modifications reserved www.schilling-marking.de